



## TX™ SERIES

### TX-10B Bridging Input Transformer



- Used to add transformer isolation to any line-level RDL product input
- Frequency response: 20 Hz to 20 kHz (+/- 0.5 dB)
- THD: , 0.05% (1 kHz)
- 10 kΩ input bridges any audio line
- Balanced input and output

### TX-LM2 Line Matching Transformer



- Matches balanced 600 Ω phone or other line into mic or line input
- Dual outputs: Unbalanced line level or balanced mic level
- Frequency response: 20 Hz to 20 kHz (+/- 0.5 dB)
- THD: < 0.05% (1 kHz)

### TX-1A Adjustable Line Transformer



- Provides transformer isolation between balanced and unbalanced line inputs
- Level trimpot adjusts output 4 to 24 dB below
- Input level may be 10 kΩ bridging or 600 Ω terminated
- Frequency response: 20 Hz to 20 kHz (+/- 0.5 dB)
- THD+N: < 0.05 % (1 kHz)

### TX-70A 100/70/25 Volt Input Interface



- Matches a 100, 70 or 25 volt speaker line to any unbalanced line-level audio input
- Trimpot adjusts output level for various input voltage/power levels
- Frequency Response: 20 Hz to 20 kHz (+/- 0.5 dB)
- THD: < 0.05% (1 kHz)

#### SPECIFICATIONS:

Width:	1.20 in.	3.00 cm
Length:	3.00 in.	7.60 cm
Height:	1.40 in.	3.60 cm