

TECHNICAL INFORMATION

4.1 SPECIFICATIONS

Audio Inputs

Dynamic Microphone Input

Type	XLR Female Balanced
Input Impedance	1200 Ω
Maximum Gain	50dB
Maximum Input Level	-10dBu
Frequency Response	10Hz to 40kHz, \pm 1dB

Input A & Input B (Left & Right)

Type	1/4" TRS Balanced
Input Impedance	10k Ω
Gain Range	-96 to +10dB

External Inputs 1-6

Type	1/4" TRS Stereo Unbalanced
Input Impedance	10k Ω
Gain Range	-96 to +10dB

Audio Outputs

Headphone Outputs 1-6

Type	1/4" TRS Active Stereo
Maximum Output	150mW/channel @ 60 Ω Load
THD+N	\leq 0.05% (150mW/channel @ 60 Ω Load)
Frequency Response	10Hz – 70kHz, \pm 1dB

Stereo Outputs 1-6

Type	1/4" TRS Stereo Unbalanced
Output Impedance	50 Ω

TECHNICAL INFORMATION

Internal Linear Power Supply

Type IEC
Input Voltage Range 100-120 VAC or 220-230 VAC (factory set)
Power Requirements (continuous) 30 Watts

Physical

Package Type 1U Steel and Aluminum Chassis
Dimensions 19" (W) x 1.75" (H) x 5.5" (D) (48.26cm x 4.45cm x 13.97cm)
Weight Approximately 5 lbs.

As a commitment to constant improvement, PreSonus Audio Electronics, Inc. reserves the right to change any specification stated herein at any time in the future without notification.