

# EVID FM 6.2

## Inwall Speaker System

The FM6.2 provides very high power handling and outstanding audio performance in a fully sealed in wall speaker system package. It is perfect for installations in larger rooms and it features a 6" woofer coupled with a 6" passive radiator for extended bass response. A 1" dome tweeter gives clean sound out to 20 kHz. It's all housed in a shallow, fully sealed enclosure for consistent audio quality and superior sound isolation from adjacent rooms.

### Specifications

Frequency Response (-10dB)	52 - 20000 Hz
Sensitivity 1W/1m	90 dB
LF Transducer	6inch with 6inch passive radiator
HF Transducer	1 inch Titanium dome tweeter
Nominal Impedance (Passive)	8 Ohms
Enclosure Material	Zinc Plated Metal
Transformer Taps (Transformer Version Only)	7.5, 15, 30, 60w at 70v

Weight Net

5.8 kg ( 12.79 lbs )

Dimensions (HxWxD)

465 x 256 x 100.3 mm  
(18.31" x 10.08" x 3.95")**Related Press Releases**

[Electro-Voice® presents EVID FM series flush mount in-wall speakers: a unique combination of performance, strength, and style](#)

[SE-42/62 Instruction Sheet](#)

[EVID Inwall Speaker System ...](#)

**Downloads**

[EVID FM 6.2 EDS Sheet](#)

**Accessories****[SE-62](#)**

The EVID SE-62 is a surface mount enclosure kit which enables the EVID FM6.2 InWall speaker system to be mounted on a wall without cutting a hole. The kist is sold in pairs and consists of two enclosures and all necessary hardware for mounting.

[Bosch Communications Systems](#)

