

SENNHEISER

ew 300 IEM G3 Monitoring System

The ew 300 IEM G3 system features an adaptive-diversity receiver, ear-canal phones with various ear-fitting pads for an individual fit, pass-through outputs, 5-band equalizer integrated into the transmitter, and remote computer control via Ethernet and Sennheiser's Wireless Systems Manager software. Automatic frequency scan, adjustable limiter, stereo/focus modes, and more.



Inv#	Model#	List	M.A.P.
56315	ew300IEMG3	SR 300 IEM G3 Transmitter/EK 300 IEM G3 Receiver/IE4 earbuds	1499.99 999.95

audio-technica

M2 Wireless In-Ear System

Audio Technica's 100 channel M2 in-ear monitoring system features three receiver modes: Stereo, Mono, and Personal Mix Control, giving each performer individual control over volume and mix. This complete system includes an M2R receiver, EP3 dynamic earphones (with 3 earpiece sizes and foam tips), and an M2T transmitter featuring 2 XLR-1/4" combo inputs, XLR loop output, limiter, and auxiliary input. Up to ten M2 systems can be used simultaneously.



Inv#	Model#	List	M.A.P.
52394	M2L	100ch/M2R Receiver/M2T Transmitter/Earphones/L Band	799.00 599.00
52395	M2M	100ch/M2R Receiver/M2T Transmitter/Earphones/M Band	799.00 599.00

SHURE

PSM 200® Personal Monitor System

The Shure PSM 200® Personal Monitor System is designed as an alternative to floor wedges. The P2T TransMixer features 2 XLR-1/4" inputs with individual level controls, allowing the user to mix any two source signals. The P2R hybrid bodypack can function as a wired receiver, wireless receiver, or both simultaneously. The SE 115 earphones include three sizes of foam and flex sleeves. Together, these components form a superb entry level in-ear system.



Inv#	Model#	List	M.A.P.
6462	P2TR115CL	8 Channel/P2T TransMixer/P2R Receiver/SE 115-CL Earphones	749.00 599.00
81495	P2R115CL	P2R Receiver/SE 115 Earphones/No TransMixer	411.00 329.00

SHURE

PSM 900® Monitor System

The PSM 900® system consists of the P9T transmitter and P9R bodypack receiver. Shure's patented Audio Reference Companding allows the PSM 900 to sound more like a wired system than ever before. Up to 20 transmitters can be used simultaneously per frequency range. CueMode allows monitoring of stage mixes. Other features include Scan mode, IR Sync, MixMode® Technology, and an easy to use LCD menu.



Inv#	Model#	List	M.A.P.
59927	P9TR425CL	P9T transmitter, P9R Receiver, SE425CL Sound Isolating™ Earphones	1800.00 1330.00
59925	P9TR	P9T transmitter, P9R Receiver, no Earphones	1650.00 1099.00
59926	P9R	PSM 900 Bodypack Receiver	676.00 450.00

LOOK for The Icons!

They'll help you spot key features at a glance and make comparing products easier than ever. See the Icon Legend on the opposite page footer.

AKG 4 Wireless In-Ear Monitor System

AKG's IVM 4 wireless in-ear monitor system integrates dbx® dynamics processing, providing compression, limiting, EQ, and binaural room simulations. This suite of processing eliminates the need for additional gear between the mixer and transmitter. The room sims provide the user with natural imaging, reducing the feeling of separation from the stage environment. This 1200 channel system includes the SST4 transmitter, SPR4 receiver and IP2 earphones.



Inv#	Model#	List	M.A.P.
51737	IVM 4	1200ch RX/TX, Earphones	1599.00 999.00

AKG GALAXY AUDIO AS-900 Fixed Frequency Personal Monitors

The AS-900 is an ideal entry-level Wireless Personal Monitor. The receiver features an RF and low battery indicator. The transmitter has a L/R level display, stereo XLR-1/4" inputs and an headphone output with volume control. The AS-900 is a single channel, fixed frequency unit with a 100' operating range.



Inv#	Model#	List	M.A.P.
58442	AS-900	AS-900T/AS-900R/Ear buds	259.99 199.99
58443	AS-900-4	Band Pack with (1)AS-900T/(4)AS-900R/Ear buds	859.95 549.99

AKG GALAXY AUDIO AS-1100 Any Spot Wireless Personal Monitor

Included with the AS-1100 are the AS-1100T transmitter and AS-1100R receiver. The AS-1100T features stereo XLR-1/4" inputs, headphone output, and an LCD screen that displays the channel and input level. The AS-1100R's screen displays channel, battery level, and RF/AF level. The system can transmit one monitor mix to any number of receivers via 120 selectable channels, with an operating range of up to 300'.



Inv#	Model#	List	M.A.P.
58440	AS-1100	AS-1100T/AS-1100R/Ear buds	559.99 399.99
58441	AS-1100-4	Band Pack with (1)AS-1100T/(4)AS-1100R/Ear buds	1469.95 999.99