

TX2152

Dual 15-inch Two-way Fullrange

The Electro-Voice TX2152 excels where all other competitive dual 15-inch loudspeakers fail - transient detail. The secret is the combination of dual SMX2150 low distortion woofers with an integrated analog crossover utilizing elliptical filters that achieve 36dB per octave slopes at the crossover frequency. The result is crossover performance that rivals, or exceeds, that of many electronic DSP devices and bi-amping. To keep up with all this output, the TX2152 is the only Tour X model that employs the neodymium ND2 compression driver found in EV small and medium size line arrays. The TX2152 also benefits from the outstanding pattern control of the rotate-able, larger 60° x 40° horn. The aesthetically unique Backbone grille not only looks great, but also provides greater strength and damage resistance than simple grille block designs. Proprietary ergonomically correct handles and angled input panels, and (6) 3/8-inch threaded suspension inserts make the TX2152 easy to transport and employ in a variety of applications.

Specifications

Frequency Response (-3dB)	55 - 13000 Hz
Frequency Response (-10dB)	50 - 18000 Hz
Recommended High-Pass Frequency	40 Hz
Sensitivity 1W/1m	103 dB
Max. SPL / 1m (calc)	139 dB
Coverage (nominal -6dB) H°	60 °
Coverage (nominal -6dB) V°	40 °
Rotatable Horn	Yes
System Power Handling (continuous/program/peak)	1000/2000/4000 Watts
LF Transducer	(2) SMX2151
HF Transducer	ND2
Crossover Frequency	1750 Hz
Nominal Impedance (Passive)	4 Ohms
Minimum Impedance	3.1 Ohms

Enclosure Material	Plywood and MDF with EVCOAT
Suspension	(6) 3/8-inch threaded inserts
Color	Black
Flying	Yes
Input Connections	Parallel Neutrik® NL4
Internal Crossover	Yes
Speaker Type	Fullrange
Weight Net	42.8 kg (94.36 lbs)
Dimensions (HxWxD)	1154 x 508 x 471 mm (45.43" x 20" x 18.54")



Related Press Releases

[Electro-Voice® launches new Tour X loudspeaker line at InfoComm 2008](#) **Downloads**

[TX2152 EDS](#)

[TX2152_img1](#)

[TX2152_img2](#)

[TX2152_img3](#)

[TX2152_img4](#)

[TX2152_img5](#)

[TX2152_img6](#)

[Bosch Communications Systems](#)