

# TX1181

## 18-inch Direct Radiator Subwoofer

The TX1181 is the perfect companion sub to the TX1122 and TX1152 when compact and portable performance is required. Utilizing the proven EVS18S woofer, the TX1181 effortlessly provides the low frequency energy needed to keep up with Tour X top boxes, as well as many other EV loudspeaker products. The integrated low-pass input filter allows for "single amp drive", and the high sensitivity and excellent power handling don't require an enormous, expensive amplifier to generate high SPL. The aesthetically unique Backbone grille not only looks great, but also provides greater strength and damage resistance than simple grille block designs. Proprietary ergonomically correct handles and angled input panels, and integrated screw-in style pole mount make the TX1181 easy to transport and employ in a variety of applications.

### Specifications

Frequency Response (-3dB)	50 - 160 Hz
Frequency Response (-10dB)	45 - 700 Hz
Recommended High-Pass Frequency	30 Hz
Sensitivity 1W/1m	100 dB
Max. SPL / 1m (calc)	132 dB
System Power Handling (continuous/program/peak)	500/1000/2000 Watts
LF Transducer	EVS18S
Nominal Impedance (Passive)	8 Ohms
Minimum Impedance	7.5 Ohms
Enclosure Material	Plywood and MDF with EVCOAT
Color	Black

Flying	No
Input Connections	Parallel Neutrik® NL4
Internal Crossover	Yes
Speaker Type	Subs
Weight Net	33.8 kg ( 74.52 lbs )
Dimensions (HxWxD)	769 x 439 x 591 mm (30.28" x 17.28" x 23.27")



#### **Related Press Releases**

[Electro-Voice® launches new Tour X loudspeaker line at InfoComm 2008](#) **Downloads**

[TX1181 EDS](#)

[TX1181\\_img1](#)

[TX1181\\_img2](#)

[TX1181\\_img3](#)

[TX1181\\_img4](#)

[TX1181\\_img5](#)

[TX1181\\_img6](#)

[Bosch Communications Systems](#)