

TX1152

15-inch Two-way Fullrange

The Electro-Voice TX1152 fits the bill when the low frequency extension of a 15-inch woofer is required, along with outstanding pattern control from the rotate-able, larger 60° x 40° horn. Utilizing the incredibly low distortion SMX2150 15-inch woofer, the TX1152 boasts specs normally associated with loudspeakers priced well over twice as much. The aesthetically unique Backbone grille not only looks great, but also provides greater strength and damage resistance than simple grille block designs. Proprietary ergonomically correct handles and angled input panels, integrated pole mount and (6) 3/8-inch threaded suspension inserts make the TX1152 easy to transport and employ in a variety of applications.

Specifications

Frequency Response (-3dB)	55 - 20000 Hz
Frequency Response (-10dB)	40 - 20000 Hz
Recommended High-Pass Frequency	40 Hz
Sensitivity 1W/1m	100 dB
Max. SPL / 1m (calc)	133 dB
Coverage (nominal -6dB) H°	60 °
Coverage (nominal -6dB) V°	40 °
Rotatable Horn	Yes
System Power Handling (continuous/program/peak)	500/1000/2000 Watts
LF Transducer	SMX2151
HF Transducer	DH3
Crossover Frequency	1650 Hz
Nominal Impedance (Passive)	8 Ohms
Minimum Impedance	5.6 Ohms
Enclosure Material	Plywood and MDF with EVCOAT
Suspension	(6) 3/8-inch threaded inserts
Color	Black
Flying	Yes
Input Connections	Parallel Neutrik® NL4
Internal Crossover	Yes
Speaker Type	Fullrange
Weight Net	27.8 kg (61.29 lbs)
Dimensions (HxWxD)	776 x 446 x 446 mm (30.55" x 17.56" x 17.56")



Related Press Releases

[Electro-Voice® launches new Tour X loudspeaker line at Downloads InfoComm 2008](#)

[TX1152 EDS](#)

[TX1152_img1](#)

[TX1152_img2](#)

[TX1152_img3](#)

[TX1152_img4](#)

[TX1152_img5](#)

[TX1152_img6](#)

[Bosch Communications Systems](#)