

TX1122

12-inch Two-way Fullrange

The Electro-Voice TX1122 is truly designed to be the compact over achiever of the Tour X family. Employing the same space saving 90° x 50° horn as the FM models, and the incredibly low distortion SMX2120 12-inch woofer, the TX1122 will astound you with performance that blows away competitive 15-inch two-ways. The aesthetically unique Backbone grille not only looks great, but also provides greater strength and damage resistance than simple grille block designs. Proprietary ergonomically correct handles and angled input panels, integrated pole mount and (6) 3/8-inch threaded suspension inserts make the TX1122 easy to transport and employ in a variety of applications.

Specifications

| | |
|---|-------------------------------|
| Frequency Response (-3dB) | 60 - 20000 Hz |
| Frequency Response (-10dB) | 45 - 20000 Hz |
| Recommended High-Pass Frequency | 45 Hz |
| Sensitivity 1W/1m | 97 dB |
| Max. SPL / 1m (calc) | 130 dB |
| Coverage (nominal -6dB) H° | 90 ° |
| Coverage (nominal -6dB) V° | 50 ° |
| Rotatable Horn | No |
| System Power Handling (continuous/program/peak) | 500/1000/2000 Watts |
| LF Transducer | SMX2120 |
| HF Transducer | DH3 |
| Crossover Frequency | 1750 Hz |
| Nominal Impedance (Passive) | 8 Ohms |
| Minimum Impedance | 5.4 Ohms |
| Enclosure Material | Plywood and MDF with EVCOAT |
| Suspension | (6) 3/8-inch threaded inserts |

| | |
|--------------------|--|
| Color | Black |
| Flying | Yes |
| Input Connections | Parallel Neutrik® NL4 |
| Internal Crossover | Yes |
| Speaker Type | Fullrange |
| Weight Net | 20.2 kg (44.53 lbs) |
| Dimensions (HxWxD) | 616 x 382 x 380 mm (24.25" x 15.04" x 14.96") |



Related Press Releases

[Electro-Voice® launches new Tour X loudspeaker line at Downloads InfoComm 2008](#)

[TX1122 EDS](#)

[TX1122_img1](#)

[TX1122_img2](#)

[TX1122_img3](#)

[TX1122_img4](#)

[TX1122_img5](#)

[TX1122_img6](#)

[Bosch Communications Systems](#)