

LB5-3PT-KIT

Lyra Half x 1 Bi-Color 3-Point Soft Panel LED Light Kit

ONE SHEET

Overview

Quality and affordability successfully combine together with the Lyra 3-Point Bi-Color Soft Light Kit. Designed specifically for the professional shooter, this incredible kit features high CRI LED chips paired with a soft diffusion panel. The Lyra Bi-Color Adjustable Half x 1 panel allows you to dial in any color temperature ranging from 3200K to 5600K. It includes a wide, 110° beam angle, which provides the extra advantage of a nice, clean single shadow for subject lighting.

Adjusting color brightness is simple with a push of the large yellow button (on the back). Add to that the strong steel tension knobs and 30° yoke allow you to use the light in any production environment! The large digital LED readout also makes it easy to quickly reference the light output with clear accuracy. This versatile light kit comes with Gold and V-Mount battery plates as well as intensifiers.

The Lyra 3-Point light kit is ideally used for Documentary and ENG/EFP purposes. It includes three Lyra Half x 1 Bi-Color lights, three heavy-duty stands, one light bag, and one stand bag. With an equivalent wattage of a 350-Watt (incandescent) soft light and a power draw of 150-Watts, the Lyra 3-Point Light Kit has it all!



LB5-3PT-KIT | Lyra Half x 1 Bi-Color 3-Point Soft Panel LED Light Kit | **UPC Code:** 847983017492

Special Features

- High CRI Chip LEDs paired with 1/2 stop soft diffusion panel
- Bi-Color adjustable from 3200K-5600K
- Bright consistent light across all color temperatures
- Beam Angle: 110 degrees
- Clean single shadow without artifacts
- Baby 5/8 inch/Junior 1-1/8 inch Combo Pin adapter with right angle receiver hole
- 30 degree angled yoke for unobstructed movement

Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseet



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LB5-3PT-KIT

Features you need, Prices you want.

Strong, Bright Light

The high CRI LED chips and 1/2-Stop spot diffusion panel can output a strong, bright diffused light.

Bi-Color Adjustability

With a 3200K-5600K Bi-Color adjustable range, these Lyra soft lights work well in any lighting production.

Consistently Bright

What sets Lyra soft lights apart from the competition is their ability to deliver a consistently bright light across all color temperatures at all times!

Wide Beam Angle

Each Lyra soft light features a 110° beam angle that provides a large amount of soft light all on its own.

Clean Single Shadow

Lyra's Soft Lights create single shadows that produce more of a natural, clean shot.

Combo Pin Adaptor

The Baby 5/8" & Junior 1-1/8" combo pin adaptor makes it easy to attach to any grip stand.

Unobstructed Movement

The 30° angled yoke provides the Lyra lights with unobstructed movement.

Steel Tension Knobs

The new steel tension knobs are built to be stronger and more secure. This allows you to lock the light in place at any angle.

Adjusting Brightness

A single knob makes it easy to adjust both brightness and color temperature.

LED Readout

The new LED readout is much brighter and provides precise adjustments of light output.

Batteries Included

Gold and V-Mount battery plates offer you the flexibility you need to stay on-the-go.

Barn Doors & Intensifiers

Ikan's reliable barn doors with intensifiers allow you to easily shape the light to suit your needs.

Incandescent Equivalent

The Lyra LED soft light is equivalent to a 350-Watt incandescent soft light.

RF Remote

Controlling multiple lights at a distance is possible with the RF remote control. You can turn the light ON/OFF without issues.

Max Power Draw

The Lyra Bi-Color LED Soft Light has a maximum power draw of 150-Watts, allowing you to plug it into any wall outlet.

Specs

Beam Angle	110°
Build Material	Heavy Duty Resin Plastic
Control	Knob Control
Cooling System	Passive Cooling
Dimming	Knob Control
Fixture Size	14 x 8 x 3 In.
Fixture Weight	4 lbs
Head Type	Bi-Color 3200-5600K
Lens	1/2 Stop Soft Diffusion
Light Source	510 0.2 Watt LEDs
Power Supply	Input: 110-220 VAC Output: 15 VDC
Rating	51W, 14-18VDC
Yoke	Baby 5/8" & Junior 1-1/8" combo pin
Shipping Dimensions	20 x 20 x 20 In.
Shipping Weight	29 lbs

Accessories

KCP-703	Stage Clamp w/ 16mm Stud
SW-04	Safety Wire
CV600	Chrome Exposure/Spectrometer from UPRtek
HD-STND	Heavy Duty Light Stand
ROLLR-STND10	2 Stage Roller Stand 10 ft 6 in

What's Included

- 1 x Light Bag
- 1 x Stand Bag
- 3 x Gold Mount Battery Plate
- 3 x HD Stands
- 3 x Half x 1 Light Fixture
- 3 x Power Supply with Cable
- 3 x Remote Control
- 3 x V-Mount Battery Plate
- 3 x Yoke Mount
- 3 x Safety Chain



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com