

15" High Bright Beam Splitter Teleprompter

Overview

The PT3500 teleprompter system is designed for professionals needing to work quickly and efficiently in the field or studio.

Featuring solid, aluminum and steel construction, The PT3500 is a durable yet lightweight compact 15" teleprompter kit. The foundation is a 15mm Rod base system, which allows for simple height adjustments and a folding glass frame that makes it easy for you to set up and travel.



Special Features

- Adjustable Glass Frame
- Based on 15mm Rod System
- Lightweight & Compact Design
- Ships in Reusable Foam for Easy Transport
- High Quality American Made 70/30 Teleprompter Glass

Specifications

Aspect Ratio	4:3
Brightness	1000 cd/m2
Build Material	Aluminum / Steel
Contrast Ratio	500:1
Diagonal	15"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Operating Volts	DC 12v / 4A
Power Consumption	10 w
Reading Range	20'
Resolution	1920 x 1080
Supported Video Signals	0-65 C
Viewing Angle	160° (H) / 140° (V)
Weight	15 lb
Shipping Weight	21 lb
Shipping Dimensions	29.5" x 19" x 10.5"

Recommended for

Location/Studio

What's Included

- | | |
|--|--------------------------|
| 1 x Teleprompter Base Assembly w/ Glass | 2 x 200mm Riser Rods |
| 1 x Camera Mount Assembly | 1 x PrompterPro Software |
| 1 x Hood | 1 x 5/32 Hex Key |
| 1 x High Bright LCD Monitor w Power Supply | 2 x DRS-01 |
| | 4 x Cork Strips |

Optional Accessories

- PT3100-G** Replacement Glass for PT3500