

Freedom Par Q9

- 100% TRUE wireless, battery-operated, quad-color (RGBA) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- Adjustable run times ensure the fixture will last the length of the event
- OLED display allows for full-text and to easily change fixture's settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Built-in glare shield protects light spillage and eye fatigue
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST®



- Weight: 4.6 lbs (2.1 kg)
- Size: 4.7 x 4.7 x 4.9 in (120 x 120 x 126 mm)

Specifications

- DMX Channels: 4, 6 or 14
- Light Source: 9 LEDs (quad-color RGBA) 6 W, (2.3A), 50,000 hours life expectancy
- Strobe Rate: 0 to 22 Hz
- Beam Angle: 14°
- Field Angle: 35°
- Illuminance: 3580 lux @ 2 m
- Beam Angle (with diffuser): 37°
- Field Angle (with diffuser): 68°
- Illuminance (with diffuser): 529 lux @ 2 m
- Lumens: 1,161
- Run Time (adjustable): 3, 5, 8, or 12 hrs
- Recharge Time: 3 hours
- Operating Frequency: 2.412 to 2.484 GHz
- Max Unobstructed Distance: 600 ft (183 m)
- Input Voltage: 24 VDC, 1.5 A (external power supply: 24 VDC, 50/60 Hz)
- Power and Current: 31 W, 0.3 A @ 120 V, 60 Hz
- Power and Current: 30 W, 0.2 A @ 230 V, 50 Hz
- Mounting Hole: M12
- Optional Controllers: RFC, RFC-XL, FlareCON
- Approvals: CE, UKCA, RoHS, FCC

