

# SPECIFICATIONS

<b>Frequency Response:</b> .....	10Hz—20KHz +/-3dB
<b>Total Harmonic Distortion (THD) + Noise:</b> .....	0.1%
<b>S/N Ratio:</b> .....	>60dB
<b>Tone Controls</b>	
<b>Bass:</b> .....	+/-12dB / 100Hz
<b>Treble:</b> .....	+/-12dB / 10KHz
<b>Inputs:</b> .....	6 X MIC (level/impedance): Balanced: 3mV
.....	6 X LINE(level/impedance): Unbalanced: 100mV
<b>Outputs (All controls flat)</b>	
<b>High Output:</b> .....	1.5V
<b>Low Output:</b> .....	0.5V
<b>Impedance (1/4"): .....</b>	600 ohms
<b>(XLR): .....</b>	600 ohms
<b>LED indicator:</b> .....	Power ON
<b>Fuse Requirements, Type and Size:</b> .....	T250mA, 5X20mm glass type
<b>Dimensions:</b> .....	19" x 1.75" x 8" (483 x 44 x 203mm)
<b>Weight:</b> .....	7.0 lbs.( 3.2 Kg)

*The specifications above are correct at the time of printing of this manual. For improvement purposes, all specifications for this unit, including design and appearance, are subject to change without prior notice.*