

SPECIFICATIONS

RF Carrier Frequency Range

10 to 1,000 MHz

Voltage Wave Standing Ratio (VSWR)

1.2

Impedance

50 Ω

Isolation

20 dB

Insertion Loss

2 dB

Overall Dimensions

63.5 mm x 48.2 mm x 22.3 mm (2.5 in. x 1.9 in. x 0.9 in.)

Weight

45.3 g (1.6 oz)

FURNISHED PARTS

0.5 m (2 ft.) Coaxial Antenna Cable (4).....	UA802
BNC Bulkhead Adapters, lockwasher, nut (2).....	95A8647
BNC Male-to-Male Adapter (2).....	95A8738

OPTIONAL ACCESSORIES

1/2 Wave Antenna (774-865 MHz).....	UA820A
1/2 Wave Antenna (662-698 MHz).....	UA820C
1/2 Wave Antenna (554-590 MHz).....	UA820D
1/2 Wave Antenna (756-784 MHz).....	UA820E
1/4 Wave Antenna.....	UA400
7.6 m (25 ft.) Coaxial Antenna Cable	UA825
15.2 m (50 ft.) Coaxial Antenna Cable	UA850
33 m (100 ft.) BNC-to-BNC Cable.....	UA8100
Remote Antenna Bracket with BNC Bulkhead Adapter	UA505
Antenna Rack Panel with Cables and BNC Adapters.....	UA440