

High-Fidelity Ceiling Speakers

Models HFCS1 and HFCS1LP



Description

The Bogen HFCS1 and HFCS1LP ceiling loudspeakers deliver superior sound and clear intelligibility in a variety of ceiling environments.

The system can be easily installed in hard-surfaced ceilings, suspended ceilings, and new constructions.

Both speakers offer several levels of power output controlled via a front-mounted rotary tap selector switch (under grille). The low-distortion speaker design, coupled with a computer-matched venting system, delivers high intelligibility and exceptional low-frequency response for both music and speech reinforcement.

Features

- Wide-dispersion coaxial driver for broad, even coverage
- Good off-axis response with smooth contouring
- Computer-matched venting system for full bass output
- Large back can for deeper bass response (HFCS1)
- Low-profile housing allows greater range of installations (HFCS1LP)
- High power handling capability for foreground sound
- Selectable power taps via front-mounted control
- Power taps (in watts) - 32, 16, 8, 4, 2, and 1
- 16-ohm input for non-transformer, multi-speaker systems (selectable via tap selector switch)
- Compounded rubber surround, plus polypropylene and polycarbonate drivers for lasting performance
- Easy wiring with plug-in connector
- Connector provides loop-through terminals for the next speaker
- Integral swing-out clamps for easy installation
- Attachment point for seismic cable (safety cable)
- Input terminal cover with knockouts and safety eyelet provides protection for connections
- Off-white textured finish easily painted to match theme decor
- Attractive, contemporary, sturdy steel grille assembly with fine perforations
- Accessory tile bridge support ring (Model TBCR, sold separately)
- Accessory 10-foot long cable kit (Model CK10, sold separately)

Technical Specifications

SPECIFICATIONS	HFCS1	HFCS1LP
Frequency Response (-10 dB)*	65 Hz to 19 kHz	78 Hz to 19 kHz
LF Driver	6-1/2" (165mm) Polypropylene Cone	
HF Driver	3/4" (20mm) Polycarbonate Dome	
Sensitivity (1W/1M)	89 dBspl (Average 100 Hz - 10 kHz)	
Impedance Ratings	Low (16 ohms) / High (70V/100V)	
Power Input (Max.)	75W @ 16 ohms; 32W @ 70V/100V	
Power Settings (in watts)†	70V: 32, 16, 8, 4, 2, 1 / 100V: 32, 16, 8, 4, 2	
Baffle Material	Fire-rated (94VO) ABS	
Back Can Material	Heavy-Gauge Plated Steel	
Terminations	4 Terminal Plug-in Input Connector	
Product Weight	9 lb.	7-3/4 lb.
Speaker Dimensions	12-5/16" dia. x 12" D	12-3/16" dia. x 7-3/4" D
Minimum Vertical Clearance Requirement	11"	6-3/4"
Included Accessories	Input Terminal Cover (2 Halves); (4) Screws; (1) Plug-in Input Connector	
Optional Accessories	Tile Bridge Support Ring (TBCR); Cable Kit (CK10)	
Baffle Ring & Grille Color	Off-white	

* Half-Space Response

† Front panel, switch-selected




Specifications subject to change without notice.
© 2006 Bogen Communications, Inc.
Part No. 54-8016-03B 0611

Frequency Response


Half-space,
16 Ohms,
1W @ 1m

HFCS1
HFCS1LP



Polar Response

Both speakers



Architect and Engineer Specifications

The loudspeaker shall be a Bogen Model HFCS1 or HFCS1LP Ceiling Speaker or approved equivalent, consisting of one 6-1/2" (nominal) low frequency transducer, one 3/4" (nominal) high frequency transducer, and a filter network for dividing frequencies between the transducers.

The front baffle shall be injection-molded ABS material and the back can (enclosure) shall be plated steel. All components shall be mounted inside the enclosure.

The baffle shall be supplied in off-white with a mild texture finish to promote paint adhesion, if desired. A perforated steel speaker grille shall be provided, color-matched to the baffle.

The low-frequency driver shall utilize a molded polypropylene diaphragm (cone). A compounded rubber cone surround shall be formulated to withstand environmental conditions with high or low heat, high or low humidity, and ultra-violet light.

The high-frequency driver shall utilize a diaphragm consisting of black polycarbonate.

Integral swing-out clamps shall provide a secure installation in the ceiling surface. A safety cable attachment point shall

be included in the removable terminal enclosure cover. An optional 10-foot long cable kit shall be available to serve as a backup safety cable (Model CK10). An optional tile bridge/support ring installation bracket shall provide additional support when mounting the loudspeaker into suspended ceilings (Model TBCR). The bracket shall also serve as a pre-installation guide for new construction installations, and provide attachment to either 16" OC or 24" OC mounting.

The input connector shall be a 4-screw pluggable input connector, providing loop-through terminals for additional speakers.

Power input selection shall be via a front-mounted rotary switch, located under the removable grille. High impedance tap selections shall be 1, 2, 4, 8, 16, and 32 watts. A low impedance 16-ohm selection shall also be provided.

Dimensions of the speaker shall not exceed 12-5/16" diameter x 12" D (HFCS1) or 12-5/16" diameter x 7-3/4" D (HFCS1LP). The speaker shall require a minimum vertical clearance of 11" (HFCS1) or 6-3/4" (HFCS1LP). Weight shall be 9 lb. (HFCS1) or 7-3/4 lb. (HFCS1LP).

BOGEN[®]
COMMUNICATIONS, INC.

50 Spring Street, Ramsey, New Jersey 07446, U.S.A.
201-934-8500 FAX: 201-934-9832
www.bogen.com