

ZX5

Specifications

	Zx5-60	Zx5-90
Frequency Response* (-3 dB)		58 Hz - 15 kHz
Frequency Response* (-10 dB)		41 Hz - 20 kHz
Power Handling (long term/Peak)		600W/2400W
Sensitivity 1W/1m		98 dB
Max SPL (calc.)		132 dB
Low Frequency Driver		DVX3150, 15" woofer
High Frequency driver		ND2, 2" voice coil compression driver
Box Tuning Frequency		50 Hz
X-over frequency		1500 Hz
Impedance (nom./min.)		8 Ohms / 6.5 Ohms
Dispersion (H x V)	60° x 60°	90° x 50°
Input connector		Speakon NL4 (Black and white version) Gland Nut with SOJ Cable (PI versions)
Suspension:		5 location point points for single-stud attachment plates (2 on top, 2 on bottom, 1 on rear), 3 anchor plates equipped. 10 metric inserts (M8) integrated polmount adapter
Environmental Spec:		IEC529 IP24 / IP44 for PI version
Dimensions H/W/D	686mm x 445mm 406mm	(27.00" x 17.50" x 16.00")
Net Weight/ Shipping Weight		21.3kg (41 lbs) 23.2kg (51 lbs)

* Half Space

Americas

Telex Communications Inc. 12000 Portland Ave South, Burnsville, MN 55337, USA
USA-Phone: 1-800-392-3497, Fax: 1-800-955-6831
Canada-Phone: 1-866-505-5551, Fax: 1-866-336-8467
Latin America-Phone: 1-952-887-5532, Fax: 1-952-736-4212

Europe, Africa & Middle-East

Telex EVI Audio GmbH. Hirschberger Ring 45, D 94315, Straubing, Germany
Phone: +49 9421-706 0, Fax: +49 9421-706 265
France: EVI Audio France S.A. Parc de Courcerin, All'Èe Lech Walesa, F 77185 Lognes, France
Phone: +33 1-6480-0090, Fax: +33 1-6006-5103
UK: Shuttlesound Ltd., The Willows Centre, Willow Lane, Mitcham, Surrey CR4 4NX, UK
Phone: +44 208 646 7114, Fax: +44 208 640 7583

Asia & Pacific Rim

Japan: EVI Audio Japan Ltd. 5-3-8 Funabashi, Setagaya-Ku, Tokyo, Japan 156-0055
Phone: +81 3-5316-5020, Fax: +81 3-5316-5031
China: EVI Audio (HK) Ltd. 7th Floor China Minmetals Tower, No. 79 Chatham Road South,
Tsim Sha Tsui, Kowloon, HK, Phone: +852 2351-3628, Fax: +852 2351-3329
Singapore: Telex Pte. Ltd. 3015A Ubi Road 1, 05-10 Kampong Ubi Industrial Estate, Singapore 408705
Phone: +65 6746-8760, Fax: +65 6746-1206