




GBB Series (GBB36 shown)



GBB Series Dimensions

Description

Vertical Grounding Bus Bar Series GBB is fabricated of solid copper for proper grounding of connected equipment. The Series also functions as a wire lacing bar with a wide array of lacing slots and wire tie-down points to provide organized vertical wire management within a rack or cabinet. Choose 36" long Model GBB-36 for use in racks with panel mounting space of 19-44RU. Model GBB-72 is 72" long for use in racks with panel mounting space of 44RU or greater.

Each bar features tapped holes (10-32) on EIA spacing along one side. Each bar is additionally equipped with .312" holes and obrounds size .375" \times 1.5" and .375" \times 3" for installation to the mounting rail supports (hat sections) on lowell adjustable-rail racks and cabinets. 1/4-20x5/8" screws, insulation washers and slide nuts are provided for installation.

A & E Specifications

The vertical Grounding Buss Bar for rackmount use shall be Lowell Model _____(GBB-36, GBB-72) with a overall size of ______(36"L x 2"W, 72"L x 2W). The grounding bar shall have tapped 10-32 holes along one side plus oblong slots for mounting. The grounding bar shall be made of solid copper. Installation hardware shall be provided.

Model	Description	Size	Wiring Provisions	Weight	Mounts Racks with Panel Space Height
GBB-36	Vertical Grounding Bus bar	36"L x 2"W	Includes lacing slots and wire-tie holes	4 lbs.	19-44RU
GBB-72	Vertical Grounding Bus bar	72"L x 2"W	Includes lacing slots and wire-tie holes	8 lbs.	44RU





Panel Mounting Screws (order separately)



RSP RS RSV
Phillips Phillips Torx®
Finish Head Truss Head Star Post Head

NEW RSR Robertson square head available!



RSP-500 / RS-500 Jars

ALL screws	have 5.1 hardness and include PilotPoint™ tip and (captive washer!
Model	Description	Quantity
RSP-25	Hdwr phillips finish head pilot pt w washers Blk 10-32x.875	25 pc bag
RSP-100	Hdwr phillips finish head pilot pt w washers Blk 10-32x.875	100 pc bag
RSP-500	Hdwr phillips finish head pilot pt w washers Blk 10-32x.875	500 pc jar
RS-25	Hdwr phillips truss head pilot pt w washers Blk 10-32x.875	25 pc bag
RS-100	Hdwr phillips truss head pilot pt w washers Blk 10-32x.875	100 pc bag
RS-500	Hdwr phillips truss head pilot pt w washers Blk 10-32x.875	500 pc jar
RSR-50	Hdwr robertson SQ- head pilot pt w washers Blk 10-32x.875	50 pc bag
RSR-BIT	Hdwr torx pin drive bit for RSR Series screws	1 Qty
RSV-50	Hdwr torx star post security pilot pt w washers Blk 10-32x.875	50 pc bag
RSV-BIT	Hdwr torx pin drive bit for RSV Series screws	1 Qty

Panel Space Reference Guide per EIA Standards

	ory Panel Space	Cabinet Panel Space	EIA Holes Used / Covered	
Height - Nominal (Inches) (Rack Units - RU)		Opening - Actual (Inches)	per Mounting Rail (Spaced .625"625"5")	
1.75	1	1.875	3	
3.50	2	3.625		
5.25	3		9	
7.00	<u>3</u> 4	7.125	9 12	
8.75	5	8.875	12 15	
10.50	<u> </u>		15 18	
12.25	<u> </u>	12.375	21	
			24	
14.00	8	14.125		
15.75 17.50	9 10	15.875 17.625	27 30	
19.25	11	19.375	33	
21.00	12	21.125	36	
22.75	13	22.875	39	
24.50	14	24.625	42	
26.25	15	26.375	45	
28.00	16	28.125	48	
29.75	17	29.875	51	
31.50	18	31.625	54	
33.25	19	33.375	57	
35.00	20	35.125	60	
36.75	21	36.875	63	
38.50	22	38.625	66	
40.25	23	40.375	69	
42.00	24	42.125	72	
43.75	25	43.875	75	
45.50	26	45.625	78	
47.25	27	47.375	81	
49.00	28	49.125	84	
50.75	29	50.875	87	
52.50	30	52.625	90	
54.25	31	54.375	93	
56.00	32	56.125	96	
57.75	33	57.875	99	
59.50	34	59.625	102	
61.25	35	61.375	105	
63.00	36	63.125	108	
64.75	37	64.875	111	
66.50	38	66.625	114	
68.25	39	68.375	117	
70.00	40	70.125	120	
71.75	41	71.625	123	
73.50	42	73.625	126	
75.25	43	75.375	129	
77.00	44	77.125	132	
11.00	77	11.123	132	

J

>

又

S

Open Frame Floor

Solid Side Floor & Desk

Wallmount Surface & Recessed



Thermal & Wire Mngmt