



Speakon to Speakon

Fat Max 8 AWG - Speakon to Speakon (NL4FXs)

Pro Co 11 gauge 4-conductor speaker wire, twinned to create the industry's first 8 gauge 2-conductor assembly. Two 11 gauge conductors are crimped together into an 8 gauge lead (ending up with a single circuit, 1+ and 1- on the Speakon). The leads are then inserted into the terminals on the NL4FXs and crimped down using the Speakon screws provided.

Model Number

Length in Feet

FMNN-3	3
FMNN-6	6
FMNN-10	10
FMNN-25	25
FMNN-50	50

Power Plus 12 AWG cable - Speakon to Speakon

(NL2FCs) Pro Co ArmorFlex jacketed 12 gauge 2-conductor portable speaker wire with a Neutrik Speakon (NL2FC) on each end.

S12NN-10	10
S12NN-25	25
S12NN-50	50
S12NN-100	100

Excellines 14 AWG cable - Speakon to Speakon

(NL2FCs) Pro Co ArmorFlex jacketed 14 gauge 2-conductor portable speaker wire with a Neutrik Speakon (NL2FC) on each end.

S14NN-3	3
S14NN-6	6
S14NN-10	10
S14NN-25	25
S14NN-50	50

Excellines 16 AWG cable - Speakon to Speakon

(NL2FCs) Pro Co ArmorFlex jacketed 16 gauge 2-conductor portable speaker wire with a Neutrik Speakon (NL2FC) on each end.

S16NN-3	3
S16NN-6	6
S16NN-10	10
S16NN-25	25
S16NN-50	50