

Technical Specifications

WEIGHT & DIMENSIONS

Length.....	210 mm (8.25 in)
Width.....	194 mm (7.65 in)
Height.....	70 mm (2.75 in)
Weight.....	2.3 Kg (5 lbs)

POWER

Switch-selectable power setting.....	115V 60 Hz or 230V 50 Hz
European version.....	240V 50 Hz
AC input.....	3-prong IEC 60320 C14
AC outputs.....	(8) NEMA 5-15R receptacles
AC output (115V).....	10A/Channel, Max 20A
AC output (230V).....	5A/Channel, Max 10A

FUSE

Main (115V).....	(4) 20mm Glass 10A 125V Fast Blow
Main (230V).....	(4) 20mm Glass 6.3A 250V Fast Blow

CONTROL & PROGRAMMING

Data input.....	locking 3-pin XLR male socket
Data output.....	locking 3-pin XLR female socket
Data pin configuration.....	pin 1 shield, pin 2 (-), pin 3 (+)
Protocols.....	DMX-512 USITT
DMX Channels (Mode CH:04).....	4
DMX Channels (Mode CH:02).....	2
DMX Channels (Mode CH:01).....	1

ORDERING INFORMATION

Dimmer/Relay Pack.....	DMX-4
Fuse 10A.....	P170FUSE010
Fuse 6.3A.....	P170FUSE007