



# CONVENIENCE ACCESSORIES FOR 19" WIDE CABINETS

Monitor Housings,  
Roller Trucks, Casters,  
Leg Levelers, Mounting Rails



CT-1020



CS-5PR



CS-HDPR



CS-LDPR



LL-1



LL-2

## ROLLER TRUCKS

**CT1020.** Heavy-duty, welded 16-ga. CRS roller truck provides mobility for 18½" deep cabinets. Model includes 1-pair rigid and 1-pair locking swivel casters. Casters are zinc-plated and include black, hard-tread 3" wheels. Please specify color.

MODEL	DIMENSIONS		LOAD CAPACITY	MOUNTS
	H (ADD TO RACK)	L x W		
CT1020	4" (102mm)	24 <sup>9</sup> / <sub>16</sub> " x 20 <sup>13</sup> / <sub>16</sub> " (624 x 529mm)	400 lbs. (181 kg)	(WA)100, (WA)200

## ROLLER TRUCK & CASTER KIT ACCESSORIES

**CT1020.** Heavy-duty, welded 16-ga. CRS roller truck provides mobility for 19" W x 18½" D cabinets. Unit is designed for single-bay use and has one pair rigid and one pair locking 3" swivel casters. Finish is black.

**CT-500K.** Caster kit provides mobility to 19" W x 18.5" D WA100, WA200, and 500 Series cabinets in single or multi-bay installations. Kit includes four swivel 2" dia. twin casters (two non-locking and two rigid), and two 17" L brackets with hardware.

**CT-5020K.** Caster kit provides for caster installation onto 19" W x 25½" D cabinets in single or multi-bay installations. Kit includes four, non-locking, 2½" dia. casters, and two, easy-to-install, 25" L mounting/supporting brackets. Model accommodates the 25.5" D WA202 and 502 Series cabinets.

**CT-5030K.** Caster kit for 19" W x 30" D Series 503 is similar to the CT-5020K model with a longer mounting bracket.

## CASTERS

**CS-5PR\*** These 3" dia. swivel casters mount easily to cabinets with pre-installed caster plates. Casters are zinc-plated and include black, non-locking hard-tread wheels. The load-bearing capacity is 125 lbs. each. Sold in pairs. Fits 5000 Series and Series VI.

**CS-8PR.** Locking, 3" diameter swivel casters easily mount cabinets with pre-installed caster plates. Units have a load-bearing capacity of 125 lbs. each and are sold in pairs. Casters are zinc-plated and include black, hard tread wheels. Each rack requires four casters (2 pairs).

**CS-HDPR.\*** Heavy-duty, 2½" dia. non-locking swivel casters have a load-bearing capacity of 255 lbs. ea. and will mount Series VI consoles and Series V cabinets equipped with integral caster plates. Units are zinc-plated and include black, hard-tread wheels. Sold in pairs.

**CS-LDPR.** Smooth-riding, 2" twin-wheel casters are rug-acceptable and ideal for supporting 800 Series open racks and Series VII desks. Units provide a load-bearing capacity of 75 lbs. each and install into ½"-16 threaded stem. Finish is black. Sold in pairs.

**CT-7.** Four-caster replacement set for Model CT1020 roller truck includes one pair of locking swivel and one pair of rigid casters with 125 lb. load-bearing capacity each.

## LEG LEVELERS

**LL-1 / LL-2.** Standard and heavy-duty levelers, respectively, screw mount to cabinets equipped with leg leveler sockets to provide stabilization on uneven surfaces. Four-piece set will mount Series 5000 cabinets, Series VI consoles and Series VII desks. Each leveler is easily adjusted with standard wrenches. Model LL-1 has ¾"-16 x 1¼" rolled threads and can be used in combination with non-locking casters or as a four-piece set; LL-2 has ¾"-16 x 3" threads and includes a screw-mounted, heavy-duty hard rubber cushion with chrome cap. Model LL-2 is recommended for use as a four-piece set only.

\* 4 casters are recommended for all cabinets. Single or multi-bay.

Specifications subject to change without notice



1601 JACK MCKAY BLVD. / ENNIS, TEXAS 75119 U.S.A. / TELEPHONE: (800) 876-3333 / FAX (800) 765-3435

**230 Series.** These 11-ga. CRS mounting rails are tapped 10–32 on E.I.A. universal spacing ( $\frac{5}{8}$ "- $\frac{5}{8}$ "- $\frac{1}{2}$ " continuous centers) and finished in black. Rails are sold in pairs and include hardware for installation in Series 200, WA200, WA202, 500, 502, 503, or RX as noted.

MODEL	MOUNTS CABINET SERIES	MODEL	MOUNTS CABINET SERIES
230-24BT	RX1-24	230-61BT	(WA)200-61, WA202-61, 500-61, 502-61
230-36BT	(WA)200-36, WA202-36, 500-36, 502-36,	230-70BT	(WA)200-70, WA202-70, 500-70, 502-70
	RX1-36	230-77BT	(WA)200-77, WA202-77, 500-77, 502-77
230-42BT	(WA)200-42, WA202-42, 500-42, 502-42		

**MOUNTING RAIL HARDWARE KITS All screws have 10–32 threads.**

MODEL	HARDWARE	MOUNTS
HK-40	40 Qty. 1" Chrome Phillips & 40 Plastic Washers	All Cabinets
HK-40SB	40 Qty. 1" Black Phillips & 40 Plastic Washers	All Cabinets
HK-40CN	40 Qty. Clip-on Cage Nuts	Series 5000, VI, VII, 900P, AWR, & TMC



230-T

**ARCHITECT AND ENGINEER SPECIFICATIONS**

Television/Video Monitor housing shall be Atlas Sound Model \_\_\_\_\_ (TMC-10, TMC-15). The housing shall be of welded 16-ga. CRS, and include rails punched .281 on E.I.A. spacing. Housing shall be finished in \_\_\_\_\_ (specify color). Housing shall come complete with mounting screws and U-clips.

Casters shall be Atlas Sound Model \_\_\_\_\_ (CS-5PR, CS-8PR, CS-HDPR, CS-LDPR) with a wheel dia. of \_\_\_\_\_. The casters shall have a load-bearing capacity of \_\_\_\_\_ lbs. each and shall mount the cabinet via pre-installed caster plates (except CS-LDPR which installs via  $\frac{3}{8}$ "-16 threaded stem. Casters shall be zinc plated, and include black, hard-tread wheels except CS-LDPR which is a twin, black urethane wheel.

Leveling devices shall be Atlas Sound Model \_\_\_\_\_ (LL-1, LL-2), four piece set, specified to provide stability on uneven surfaces. Each leveler shall provide threaded,  $\frac{3}{8}$ "-16, extension of \_\_\_\_\_ (1 $\frac{1}{4}$ " max: LL-1, 3" max: LL-2) using standard wrenches. Model LL-1 is one piece, finished in black, Model LL-2 shall have heavy-duty rubber cushions with a chrome cap.

Roller trucks shall be Atlas Sound Model \_\_\_\_\_ (CT1020, CT-502), of \_\_\_\_\_ ga. CRS. Model CT-502 shall be specified for mobility of multi-bay configurations and cabinets with side panels. One pair of the swivel casters shall be lockable. Casters shall be zinc-plated with black, hard-tread wheels.

Mounting rails shall be Atlas Sound Series \_\_\_\_\_ (230-T.) Rails shall be \_\_\_\_\_ ga. CRS and shall be \_\_\_\_\_ (zinc-plated and tapped 10–32 and painted: 230-T.) Rail hardware kit shall be Atlas Sound Series \_\_\_\_\_ (HK-40 or HK-40SB screws, and washers, and Model HK-40CN cage nuts where applicable.

*Specifications subject to change without notice*



1601 JACK MCKAY BLVD. / ENNIS, TEXAS 75119 U.S.A. / TELEPHONE: (800) 876-3333 / FAX (800) 765-3435