

CLOCKAUDIO

STANDS

SM 75

S 120 X

S 120 S



SM 75



S 120 S



S 120 X

SPECIFICATIONS

STANDS

SM 75

S 120 X

S 120 S

S120

Table Microphone Base fitted with M10 x 1 screw thread mounting hole

S120S

As above but fitted with Press to Talk or Latching Switch

S120X

Table Microphone Base fitted with XLR Connector

S120XS

As S120X but fitted with Press to Talk or Latching Switch

HEIGHT	S120 / S120S	1.3" (32mm)
	S120X / S120XS	2.3" (57mm) including XLR
BASE DIAMETER		4.8" (120mm)
CAVITY	The base has a cavity that can be accessed from the bottom via a metal plate secured by three screws. The space available, approx 3" (74mm) x 0.9" (22.5mm), would be suitable for mounting additional electronics.	
PACKING	6.2" x 5.4" x 2.7" (155mm x 135mm x 68mm)	
NETT/SHIPPING WEIGHT	4.1/4.3 lbs (1.87/1.95 Kilos)	

SM 75

Microphone Shock Absorbing Base for permanent fixing above or below the surface. Supplied complete with Female XLR and conversion adaptor for 3/8" BSW or 10mm screw fittings.

HEIGHT	1.3" (32mm)
	2.5" (64mm) including XLR
BASE DIAMETER	3" (75mm)
PACKING	3.2" x 4.4" x 1.6" (80mm x 110mm x 40mm)
NETT/SHIPPING	1.0/1.2 lbs (530/560 gms)

CLOCKAUDIO

Clockaudio Limited

9 Stratfield Park, Elettra Avenue, Waterlooville, Hampshire PO7 7XN

Tel: +44 (0)23 9225 1193 • Fax: +44 (0)23 9225 1201

E-mail: sales@clockaudio.demon.co.uk www.clockaudio.demon.co.uk

Clockaudio North America

18 Peladeau, N.D. Ile Perrot, Quebec, Canada J7V 7P2

Tel: (514) 453-1838 • Fax: (514) 323-3773

E-mail: info@clockaudio.com www.clockaudio.com

PROFESSIONAL
MICROPHONE
SYSTEMS