



Middle Atlantic Products, Inc.

[middleatlantic.com](http://middleatlantic.com)

96-032 / rev 2a / 06-23-06

# RK/BRK/OBRK/SRK Wooden Studio Racks

EIA/TIA Compliant

## The RK/BRK/OBRK/SRK Series 19" Equipment Racks

### Features

- High quality black woodgrain laminate finish (OBRK features high quality oak laminate finish)
- 5/8" furniture grade MDF board construction
- 11-gauge threaded rackrails, pre-installed
- Assembles easily with included hex key
- Decorative screw caps and feet provided
- Caster kit available (Standard on SRK)
- All assembly hardware included



SRK



RK/BRK



OBRK

### Architects' and Engineers' Specifications

#### RK/BRK/OBRK

EIA compliant Wooden Studio Rack shall be Middle Atlantic Products model # (B)RKX (X = total # of rackspace, refer to chart). RKX shall have a 16" depth. BRKX shall have an 18" depth. Studio rack shall be constructed of 5/8" furniture grade MDF board and shall feature a high quality black wood grain laminate finish. Model # OBRKX shall include all specifications of BRKX with a high quality oak laminate finish. Pre-installed rackrail shall be 11-gauge steel with tapped 10-32 holes in universal EIA spacing. Assembly hardware shall be 2-1/4" joint connector screws. A hex key shall be included for assembly. Black plastic screw caps shall snap into place to cover the included hardware. Studio rack shall be rated to 200 lb. weight capacity. Studio rack shall be warranted to be free from defects in material or workmanship under normal use and conditions for a period of 7 years.

#### SRK

EIA compliant Sloped Rolling Equipment Rack shall be Middle Atlantic Products model # SRK. Equipment rack shall provide a 16 rackspace lower bay and an upper 12 rackspace bay sloped back at a 25° angle. SRK shall be constructed of 5/8" furniture grade MDF board and shall feature a high quality black wood grain laminate finish. Pre-installed rackrail shall be 11-gauge steel with tapped 10-32 holes in universal EIA spacing. Assembly hardware shall be 2-1/4" joint connector screws. A hex key shall be included for assembly. Black plastic screw caps shall snap into place to cover the included hardware. Studio rack shall be rated to 200 lb. weight capacity. Studio rack includes four pre-installed casters. Studio rack shall be rated to 200 lb. weight capacity. Studio rack shall be warranted to be free from defects in material or workmanship under normal use and conditions for a period of 7 years.

#### OPTIONS (OBRK, BRK and RK)

- Set of four casters shall be model # RKW
- Additional set of rear rackrail, shall be model # RK-RRX (X = total # of rackspace)

#### OPTIONS (OBRK, BRK only)

- Smoked glass front door shall be model # RK-GD\_\_ (6, 8, 10, 12, 14, 16, 20) for \_\_ rackspace (O)BRK rack
- Quick-Position™ shelf with built-in cable management slots shall be model # SH-BRK. Shelf mounts without rackrail for OBRK/BRK and accepts horizontal mounting of PD-815SC or PD-815SC-NS power strip


electronic version available at [middleatlantic.com](http://middleatlantic.com)

## Engineered Mounting Solutions


US: New Jersey • California • Illinois • Voice: 973-839-1011 Fax: 973-839-1976 • [middleatlantic.com](http://middleatlantic.com)  
 Canada: Ontario • British Columbia • Voice: 613-836-2501 Fax: 613-836-2690 • [middleatlantic.ca](http://middleatlantic.ca)

96-032 / rev 2a / 06-23-06 / RK/BRK Wooden Studio Racks

### SRK basic dimensions



### RK/BRK/OBRK basic dimensions



PART #	A OVERALL HEIGHT	B RACKING HEIGHT	C OVERALL DEPTH
RK2	5.00 [127]	3.50 [89]	16.00 [406]
RK4	8.50 [216]	7.00 [178]	16.00 [406]
RK6	12.00 [305]	10.50 [267]	16.00 [406]
RK8	15.50 [394]	14.00 [356]	16.00 [406]
RK10	19.00 [483]	17.50 [445]	16.00 [406]
RK12	22.50 [572]	21.00 [533]	16.00 [406]
RK14	26.00 [660]	24.50 [622]	16.00 [406]
RK16	29.50 [749]	28.00 [711]	16.00 [406]
RK20	36.50 [927]	35.00 [889]	16.00 [406]
BRK6	12.00 [305]	10.50 [267]	18.00 [457]
(O)BRK8	15.50 [394]	14.00 [356]	18.00 [457]
BRK10	19.00 [483]	17.50 [445]	18.00 [457]
(O)BRK12	22.50 [572]	21.00 [533]	18.00 [457]
BRK14	26.00 [660]	24.50 [622]	18.00 [457]
(O)BRK16	29.50 [749]	28.00 [711]	18.00 [457]
(O)BRK20	36.50 [927]	35.00 [889]	18.00 [457]