



[Advanced Search](#)

[DEUTSCH](#)
[USA](#)

- [RECORDING](#)
- [STAGE](#)
- [INSTALLED](#)
- [WIRELESS](#)
- [HEADPHONES](#)
- [ACCESSORIES](#)

PRODUCTS A-Z

Product navigation
[HEADPHONES](#)

Please select

[HOME](#) » [PROFESSIONAL HEADPHONES](#) » [K 240 MK II](#)

Studio

K 240 MK II

[AKG NEWSLETTER](#)
[SECURE AREA](#)

IMAGE >

 01



K 240 MK II

[High-resolution image](#) (JPG, 3,95 MB)

- [DESCRIPTION](#)
- [SPECIFICATIONS](#)
- [ENGINEER'S SPECIFICATIONS](#)
- [STANDARD ACCESSORIES](#)
- [TECHNOLOGY](#)
- [PRESS RELEASES](#)

Type	semi-open, dynamic headphones
Sensitivity	91 dB/mW, 104 dB/V
Frequency range	15 to 25,000 Hz
Rated impedance	55 ohms
Max. input power	200 mW
Earpads	leatherette and velvet
Cable	3 m single-sided and 5 m coiled cable (99,9% oxygen-free); plug-in cable on headphones (mini-XLR connector)
Connector	gold plated stereo mini jack
Adapter	gold plated 1/8" to 1/4" screw-on adapter
Net weight (without cable)	240 g (8.5 oz.)
Shipping weight	550 g (19.4 oz.)
Patent(s)	Varimotion – multiple-thickness diaphragm for dynamic transducer (Patent no. AT 403.751, US 6,185,809, EP 814.637 (DE, DK, FI, FR, GB, IT, NL), JP 3.927.651); Acoustics slot resistor for dynamic transducer (Patent no. AT 408.706, US 6,639,991, ZL 01116806)



