



CONVENIENCE ACCESSORIES FOR 19" WIDE CABINETS

Monitor Housings,
Roller Trucks, Casters,
Leg Levelers, Mounting Rails



CT-1020



CS-5PR



CS-HDPR



CS-LDPR



LL-1



LL-2

ROLLER TRUCKS

CT1020. Heavy-duty, welded 16-ga. CRS roller truck provides mobility for 18½" deep cabinets. Model includes 1-pair rigid and 1-pair locking swivel casters. Casters are zinc-plated and include black, hard-tread 3" wheels. Please specify color.

| MODEL | DIMENSIONS | | LOAD CAPACITY | MOUNTS |
|--------|-----------------|---|----------------------|------------------|
| | H (ADD TO RACK) | L x W | | |
| CT1020 | 4" (102mm) | 24 ⁹ / ₁₆ " x 20 ¹³ / ₁₆ " (624 x 529mm) | 400 lbs. (181 kg) | (WA)100, (WA)200 |

ROLLER TRUCK & CASTER KIT ACCESSORIES

CT1020. Heavy-duty, welded 16-ga. CRS roller truck provides mobility for 19" W x 18½" D cabinets. Unit is designed for single-bay use and has one pair rigid and one pair locking 3" swivel casters. Finish is black.

CT-500K. Caster kit provides mobility to 19" W x 18.5" D WA100, WA200, and 500 Series cabinets in single or multi-bay installations. Kit includes four swivel 2" dia. twin casters (two non-locking and two rigid), and two 17" L brackets with hardware.

CT-5020K. Caster kit provides for caster installation onto 19" W x 25½" D cabinets in single or multi-bay installations. Kit includes four, non-locking, 2½" dia. casters, and two, easy-to-install, 25" L mounting/supporting brackets. Model accommodates the 25.5" D WA202 and 502 Series cabinets.

CT-5030K. Caster kit for 19" W x 30" D Series 503 is similar to the CT-5020K model with a longer mounting bracket.

CASTERS

CS-5PR* These 3" dia. swivel casters mount easily to cabinets with pre-installed caster plates. Casters are zinc-plated and include black, non-locking hard-tread wheels. The load-bearing capacity is 125 lbs. each. Sold in pairs. Fits 5000 Series and Series VI.

CS-8PR. Locking, 3" diameter swivel casters easily mount cabinets with pre-installed caster plates. Units have a load-bearing capacity of 125 lbs. each and are sold in pairs. Casters are zinc-plated and include black, hard tread wheels. Each rack requires four casters (2 pairs).

CS-HDPR.* Heavy-duty, 2½" dia. non-locking swivel casters have a load-bearing capacity of 255 lbs. ea. and will mount Series VI consoles and Series V cabinets equipped with integral caster plates. Units are zinc-plated and include black, hard-tread wheels. Sold in pairs.

CS-LDPR. Smooth-riding, 2" twin-wheel casters are rug-acceptable and ideal for supporting 800 Series open racks and Series VII desks. Units provide a load-bearing capacity of 75 lbs. each and install into ½"-16 threaded stem. Finish is black. Sold in pairs.

CT-7. Four-caster replacement set for Model CT1020 roller truck includes one pair of locking swivel and one pair of rigid casters with 125 lb. load-bearing capacity each.

LEG LEVELERS

LL-1 / LL-2. Standard and heavy-duty levelers, respectively, screw mount to cabinets equipped with leg leveler sockets to provide stabilization on uneven surfaces. Four-piece set will mount Series 5000 cabinets, Series VI consoles and Series VII desks. Each leveler is easily adjusted with standard wrenches. Model LL-1 has ¾"-16 x 1¼" rolled threads and can be used in combination with non-locking casters or as a four-piece set; LL-2 has ¾"-16 x 3" threads and includes a screw-mounted, heavy-duty hard rubber cushion with chrome cap. Model LL-2 is recommended for use as a four-piece set only.

* 4 casters are recommended for all cabinets. Single or multi-bay.

Specifications subject to change without notice



1601 JACK MCKAY BLVD. / ENNIS, TEXAS 75119 U.S.A. / TELEPHONE: (800) 876-3333 / FAX (800) 765-3435

230 Series. These 11-ga. CRS mounting rails are tapped 10–32 on E.I.A. universal spacing ($\frac{5}{8}$ "- $\frac{5}{8}$ "- $\frac{1}{2}$ " continuous centers) and finished in black. Rails are sold in pairs and include hardware for installation in Series 200, WA200, WA202, 500, 502, 503, or RX as noted.

| MODEL | MOUNTS CABINET SERIES | MODEL | MOUNTS CABINET SERIES |
|----------|---------------------------------------|----------|--------------------------------------|
| 230-24BT | RX1-24 | 230-61BT | (WA)200-61, WA202-61, 500-61, 502-61 |
| 230-36BT | (WA)200-36, WA202-36, 500-36, 502-36, | 230-70BT | (WA)200-70, WA202-70, 500-70, 502-70 |
| | RX1-36 | 230-77BT | (WA)200-77, WA202-77, 500-77, 502-77 |
| 230-42BT | (WA)200-42, WA202-42, 500-42, 502-42 | | |



230-T

MOUNTING RAIL HARDWARE KITS All screws have 10–32 threads.

| MODEL | HARDWARE | MOUNTS |
|---------|---|--|
| HK-40 | 40 Qty. 1" Chrome Phillips & 40 Plastic Washers | All Cabinets |
| HK-40SB | 40 Qty. 1" Black Phillips & 40 Plastic Washers | All Cabinets |
| HK-40CN | 40 Qty. Clip-on Cage Nuts | Series 5000, VI, VII, 900P, AWR, & TMC |

ARCHITECT AND ENGINEER SPECIFICATIONS

Television/Video Monitor housing shall be Atlas Sound Model _____ (TMC-10, TMC-15). The housing shall be of welded 16-ga. CRS, and include rails punched .281 on E.I.A. spacing. Housing shall be finished in _____ (specify color). Housing shall come complete with mounting screws and U-clips.

Casters shall be Atlas Sound Model _____ (CS-5PR, CS-8PR, CS-HDPR, CS-LDPR) with a wheel dia. of _____. The casters shall have a load-bearing capacity of _____ lbs. each and shall mount the cabinet via pre-installed caster plates (except CS-LDPR which installs via $\frac{3}{8}$ "-16 threaded stem. Casters shall be zinc plated, and include black, hard-tread wheels except CS-LDPR which is a twin, black urethane wheel.

Leveling devices shall be Atlas Sound Model _____ (LL-1, LL-2), four piece set, specified to provide stability on uneven surfaces. Each leveler shall provide threaded, $\frac{3}{8}$ "-16, extension of _____ (1 $\frac{1}{4}$ " max: LL-1, 3" max: LL-2) using standard wrenches. Model LL-1 is one piece, finished in black, Model LL-2 shall have heavy-duty rubber cushions with a chrome cap.

Roller trucks shall be Atlas Sound Model _____ (CT1020, CT-502), of _____ ga. CRS. Model CT-502 shall be specified for mobility of multi-bay configurations and cabinets with side panels. One pair of the swivel casters shall be lockable. Casters shall be zinc-plated with black, hard-tread wheels.

Mounting rails shall be Atlas Sound Series _____ (230-T.) Rails shall be _____ ga. CRS and shall be _____ (zinc-plated and tapped 10–32 and painted: 230-T.) Rail hardware kit shall be Atlas Sound Series _____ (HK-40 or HK-40SB screws, and washers, and Model HK-40CN cage nuts where applicable.

Specifications subject to change without notice



1601 JACK MCKAY BLVD. / ENNIS, TEXAS 75119 U.S.A. / TELEPHONE: (800) 876-3333 / FAX (800) 765-3435