

[Home](#) | [Professional audio equipment](#) | [Audiocontractor](#) | [Qube](#) | [Cicognani](#) | [Musical Instruments Distribution](#) | [Kempton](#)



[Company](#) | [Contacts](#) | [Dealers](#) | [Download](#) | [News](#) | [Press](#)

[Modus](#) [PSR](#) [VERVE](#) [HiMaxX](#) [FBTMaxX](#) [Jolly](#)

[Jolly 15B A](#) [Jolly 15B](#) [Jolly 15R A](#) [Jolly 15R](#) [Jolly 12B A](#) [Jolly 12B](#) [Jolly 12R A](#) [Jolly 12R](#) [Jolly 8B A](#)  
[Jolly 8B](#) [Jolly 8R A](#) [Jolly 8R](#) [Jolly 5B A](#) [Jolly 5B](#) [Jolly 5R A](#) [Jolly 5R](#) [Jolly 5B T](#) [Jolly Sub 12A](#) [Jolly Sub 10A](#)

Jolly 8B A

Processed Active Monitor 150W+50W



- 2-way bi-amped bass-reflex speaker system with 200 mm woofer and 25 mm high frequency unit
- Extremely light and sturdy enclosure made of gas injection moulded polypropylene
- Integral handle, stand adapter, 2 M6 anchoring points and a comprehensive range of accessories for fixed installations
- Custom 90° x 60° dispersion horn
- Asymmetrical trapezoidal shape for use as a stage monitor
- An ideal choice for live performance applications thanks to the reduced dimensions in relation to the hefty 119dB SPL, along with frequency response that excels in terms of linearity and extension.
- Enormous application versatility: band P.A.s, piano-bars, home and live monitors, and fixed installations in live music club venues, pubs, gyms, and all other venues requiring high sound pressure combined with compact dimensions
- Custom 200 mm high efficiency high excursion woofer
- Custom 25 mm compression tweeter
- Built-in amplifiers: 150W rms class G for the woofer and 50W rms for the high frequency unit
- ADAP® (Advanced Dynamic Active Protection) designed to limit amplifier saturation and ensure complete reliability of the system even in extreme conditions
- 24dB/oct active filters
- Control panel with: Ground-lift switch, Combo XLR/jack inputs, XLR male output, mic/line switch, 2 Band EQ – (high/low), limiter, volume control



- [Specifications](#)
- [Accessories](#)
- [Download](#)

**FBT Elettronica spa - 62019 Recanati (MC) - ITALY - tel. +39 071 750591 r.a. fax +39 071 7505920  
P.O. Box 104 - e-mail: [info@fbt.it](mailto:info@fbt.it) - IT00090690439**