



PRODUCTS

HOME

PRODUCTS

NEWS

DOWNLOADS

ABOUT ASHLY

CONTACT

NE Series 8250 Eight-channel, 250W/ch @ 4 ohms, 25V, 70V, 100V


[NE Series Multichannel Amplifier Manual](#)
[NE Series Brochure](#)
[NE8250 Series Data Sheet](#)
[High Resolution Photo \(front\)](#)
[High Resolution Photo \(back\)](#)
[Operating Software \(Protea Software Suite\)](#)
[Accessories](#)

Specifications

| Model | ne8250 ne8250pe | ne8250.25 ne8250.25pe | ne8250.70 ne8250.70pe | ne8250.10 ne8250.10pe |
|---|---------------------|--------------------------|--------------------------|--------------------------|
| Signal to Noise (20 Hz-20 kHz, unweighted) | >98 dB | >98 dB | >98 dB | >98 dB |
| Power Consumption (Pink Noise @ 4 Ohm) | | | | |
| 1/8th Output | 31.25W | 31.25W | 31.25W | 31.25W |
| 1/8th Draw | 360W | 360W | 360W | 360W |
| 1/8th Current | 4.8A | 4.8A | 4.8A | 4.8A |
| Idle Power | 35W | 35W | 35W | 35W |
| Idle Current | 0.5A | 0.5A | 0.5A | 0.5A |
| Output Circuitry: Class D | | | | |
| Input Sensitivity: 6.2dBu | | | | |
| Frequency Response: 20 Hz - 20 kHz, +/- 1.0 dB | | | | |
| Damping Factor: - 8 ohm load, > 250 | | | | |
| Input Impedance: 20 k ohms, balanced | | | | |
| Maximum Input Level: +21 dBu | | | | |
| Cooling: Temperature dependent speed-controlled fan (Front In, Side Out) | | | | |
| Front Panel Indicators per channel: Signal: -18, -12, -6,dB, Clip, Temp, Current, Bridge | | | | |
| Front Panel Indicators: overall power, standby, protect, disable, com | | | | |
| Attenuators: Per channel front panel | | | | |
| Input Connectors: each channel 3- Pin Euroblock | | | | |
| Output connectors: each channel Euroblock | | | | |
| Amplifier Protection: Output Overcurrent, DC Output, Main Supply Rail Overvoltage, Chassis Temperature, Inrush Limiting, Mains Fuse | | | | |
| Power Cable Connector: 15A Edison 3-Prong IEC | | | | |
| Dimensions 19" x 3.5" x 15.5" (88.9mm x 483mm x 394mm) | | | | |
| Weights | | | | |
| Net | 21.0 lbs (9.53kg) | | | |
| Shipping | 26.0 lbs. (11.79kg) | | | |

©2008 Ashly Audio, Inc.
 Ashly Audio, Inc. 847 Holt Road, Webster, NY 14580-9103 • Tel: 585.872.0010 • Toll Free: 800.828.6308 • Fax: 585.872.0739