

---

AtlasSound.com is best viewed with Internet Explorer 7 / Mozilla Firefox. We apologize, we are curre


[Home](#)
[Support](#)
[News](#)
[Contact](#)
[Speakers](#)
[Surface Mount](#)
[SM Series](#)
[SM52T-B](#)
[Speakers](#)
[Horns](#)
[Grilles & Back Boxes](#)
[Amplifiers](#)
[Sound Masking](#)
[Racks & Cabinets](#)
[Volume Controls](#)
[Mic Stands](#)
[Network Solutions](#)
[Other](#)

**Syn-Aud-Con**  
Corporate Member

Proud Sponsor  
**NSCA EDUCATION  
FOUNDATION**

**Tell Us About  
Your Install!**



## SM52T-B

**5 1/4" 2-Way Weather Resistant Speaker System w/ 30-Watt 70.7V/100V Internal Transformer - Black**

Environment-resistant SM Series loudspeaker systems offer quality sound reproduction and contemporary styling in a compact enclosure.

System components consist of a highly efficient woofer section and FerroFluid cooled, titanium dome high frequency device. Vocal and musical clarity is optimized by the mathematically conceived, advanced design of the Atlas Sound TRX Control WaveGuide high frequency director.

This design provides smooth, even sound coverage (90°H x 90°V). The high frequency section is symmetrical, for equal coverage in both vertical and horizontal cabinet mounting positions. High frequency component protection is provided by the Atlas Sound PolyGuard protection circuit.

The SM52T includes an internally mounted 30 Watt

adjustable tap selection for use in distributed sound applications.

To withstand the harshest environments, the new Strategy Series SM52T surface mount loudspeakers are constructed of weather resistant materials: UV-resistant, talc impregnated, polypropylene injection molded cabinets; polypropylene woofer cones; powder coated aluminum grilles and all brass hardware. The Strategy Series speaker systems include a versatile, yet simple, C-bracket designed to provide easy vertical or horizontal installation on just about any surface. Care should be taken to ensure that the chosen fixing point is strong enough to support the SM52T. Care should also be taken to ensure that the SM52T is not exposed to direct precipitation.

A 5/8"-27 threaded hole is provided on the C-bracket to allow the SM52T series speaker to be mounted on any

---

©2008 Atlas Sound LP. All Rights Reserved • [Products](#) • [About A](#)