

AT8314

Premium Microphone Cables (XLRF - XLRM)



Audio-Technica Premium Microphone Cables are engineered for maximum signal transfer and minimum loss. Designed for low-impedance operation, these balanced cables feature heavy-duty construction and professional Neutrik® connectors. To protect signal quality, each conductor has an individual spiral shield inside the molded insulating sheath. A conductive PVC layer inside each shield dissipates static buildup during flexing.

-
- Dual copper outer shields and twin conductive PVC inner shields protect cable signal quality with 100% coverage
 - Professional Neutrik® connectors ensure superior signal integrity and outstanding strain relief
 - Heavy-duty PVC jacket stands up to tough use
 - Heavy-duty 24-gauge stranded copper conductors offer optimal signal transfer
 - Extra flexibility and low memory for ease of use/storage

CABLE CONFIGURATIONS

AT8314-1.5

XLRF - XLRM balanced microphone cable. 1.5' (0.5 m) length.

AT8314-3

XLRF - XLRM balanced microphone cable. 3' (0.9 m) length.

AT8314-6

XLRF - XLRM balanced microphone cable. 6' (1.8 m) length.

AT8314-10

XLRF - XLRM balanced microphone cable. 10' (3.0 m) length.

AT8314-15

XLRF - XLRM balanced microphone cable. 15' (4.6 m) length.

AT8314-20

XLRF - XLRM balanced microphone cable. 20' (6.1 m) length.

AT8314-20R

90° XLRF - XLRM balanced microphone cable. 20' (6.1 m) length.

AT8314-25

XLRF - XLRM balanced microphone cable. 25' (7.6 m) length.

AT8314-30

XLRF - XLRM balanced microphone cable. 30' (9.1 m) length.

AT8314-50

XLRF - XLRM balanced microphone cable. 50' (15.2 m) length.

AT8314-100

XLRF - XLRM balanced microphone cable. 100' (30.5 m) length.