

# SPECIFICATIONS

---

## Frequency Response

20 to 20,000 Hz  $\pm$  0.5 dB

## Impedance

Input: 100 k $\Omega$

Output: 300  $\Omega$

## Attenuation

50 dB

## Maximum Input Signal Level

40 dBV

## Connectors

Input: 3-socket female XLR

Output: 3-pin male XLR

## Case

Full magnetic shield, steel  
with gray enamel finish

## Dimensions

19 mm (3/4 in.) diameter;

114 mm (4 1/2 in.) long

The SHURE logo is rendered in a bold, italicized, sans-serif font. The letters are thick and have a slight 3D effect, with a dark gray shadow on the right side of each letter. A registered trademark symbol (®) is located at the top right of the letter 'E'.

SHURE Incorporated <http://www.shure.com>

United States, Canada, Latin America, Caribbean:

5800 W. Touhy Avenue, Niles, IL 60714-4608, U.S.A.

Phone: 847-600-2000 U.S. Fax: 847-600-1212 Int'l Fax: 847-600-6446

Europe, Middle East, Africa:

Shure Europe GmbH, Phone: 49-7131-72140 Fax: 49-7131-721414

Asia, Pacific:

Shure Asia Limited, Phone: 852-2893-4290 Fax: 852-2893-4055