



## Dual Banana Plug to Speakon

	<b>Model Number</b>	<b>Length in Feet</b>
<b>Fat Max 8 AWG cable - Dual banana plug to 2-conductor Speakon (NL4FX)</b> Pro Co 11 gauge 4-conductor speaker wire, twinned to create the industry's first 8 gauge 2-conductor assembly, ultrasonically welded then attached to a G & H Industries gold THE BOSS dual banana plug. On the other end two 11 gauge conductors are crimped together into an 8 gauge lead (ending up with a single circuit, 1+ and 1- on the Speakon). The leads are then inserted into the terminals on the NL4FX and crimped down using the Speakon screws provided.	FMBN-3	3
	FMBN-6	6
	FMBN-10	10
	FMBN-25	25
	FMBN-50	50
<b>Power Plus 12 AWG cable - Dual banana plug to 2-conductor Speakon (NL2FC)</b> Pro Co ArmorFlex jacketed 12 gauge portable 2-conductor speaker wire with one G & H Industries THE BOSS dual banana plug and one Neutrik Speakon (NL2FC)	S12BN-10	10
	S12BN-25	25
	S12BN-50	50
	S12BN-100	100
<b>Excellines 14 AWG cable - Dual banana plug to 2-conductor Speakon (NL2FC)</b> Pro Co ArmorFlex jacketed 14 gauge 2-conductor portable speaker wire with one dual banana plug and one Neutrik Speakon (NL2FC)	S14BN-10	10
	S14BN-25	25
	S14BN-50	50
<b>Excellines 16 AWG cable - Dual banana plug to 2-conductor Speakon (NL2FC)</b> Pro Co ArmorFlex jacketed 16 gauge 2-conductor portable speaker wire with one dual banana plug and one Neutrik Speakon (NL2FC)	S16BN-10	10
	S16BN-25	25
	S16BN-50	50